

Label and Packaging Materials Inspired Brands. Intelligent World.[™]



SYS158

Fasson® 30% rPE80 Clear/S4905L/BG40#Blue Imp

30% rPE80 Clear is a clear corona treated polyethylene film with medium gloss which appearance , recycled contains 30% postmaterial from consumer waste.

Applications



Key Features

- > Clear polyethylene film with medium gloss appearance containing 30% recycled material from post-consumer waste
- > Specially engineered adhesive for use on various fabric with APEO free
- >



Facestock

A corona treated clear polyethylene film with medium gloss appearance, which contains 30% recycled material from post-consumer waste. Basis Weight: $73 \text{ g/m}^2 \pm 10\%$ ISO 536 Caliper: 0.077 mm ± 10% ISO 534

Adhesive

A general purpose permanent, acrylic emulsion adhesive. It does not contain APEO which is hazardous chemical commonly found in garment manufacturing process.

Liner

A super calendared blue glassine paper with excellent roll label converting properties.

Basis Weight:	58 g/m2 ± 10%	ISO 536
Caliper:	0.051 mm \pm 10%	ISO 534

Performance data

loop Tack (st,st)-FTM 9: 11.0 20 min 90° Peel (st,st)-FTM 2: 6.0 24 hour 90° Peel (st,st)-FTM 2: 7.0

Minimum Application Temperature: -4°C After labeling 24Hours, Service Temperature Range:-40°C~+90°C

Adhesive Performance

This is a clear, general purpose permanent adhesive with good initial tack and ultimate adhesion to a wide variety of substrates. Designed exclusively for industrial labeling applications.

S4905L is suitable for applications where compliance with FDA 175.105 is required. This section covers applications where for indirect or incidental contact food, cosmetic or drug products.

Applications and use

This product is supplied with an adhesive suitable for moderately, textured or over dyed cotton fabric apparel. There have been no cases known of fabric staining, distortion, or noticeable permanent mark when removed from fabric. However, we strongly recommend testing and scale-up trials on the actual garments intended to insure proper function. The above does not represent any guarantee or warranty and the Purchaser must independently determine the suitability of the products for the Purchaser's purposes.

Conversion/printing

The corona treated face material can be printed by letterpress, flexor, and silk screen, giving good print results with UV curing and water based inks. Cares should be taken with the heat during process.

To ensure optimum wettability and ink bond, additional in-line corona treatment is required. Ink testing is always recommended before production.

Sharp film tooling preferably in flat-bed, are important to ensure smooth conversion.

Acceptance of hot stamping foil is excellent.

Need avoid too much re-winding tension to causing bleeding.

Shelf life

One year when stored at $23 \pm 2^{\circ}$ C at $50 \pm 5^{\circ}$ RH.

Avery Dennison Label and Packaging Materials 32/F., Skyline Tower 39 Wang Kwong Road Kowloon Bay, Kowloon


Hong Kong Tel: +852 2802-9618 | +856 400 828 3797

Warranty

Warrany All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but but do no constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. AVERY DENNISON products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Any product shown to the satisfaction of AVERY DENNISON within the time provided to be so defective shall be replaced without charge of AVERY DENNISON may issue credit in such amount as it seems reasonable however, in no event shall AVERY DENNISON be respon claims beyond the replacement value of the defective product or in any way sable for

SYS158

Fasson[®] 30% rPE80 Clear/S4905L/BG40#Blue Imp



30% rPE80 Cl	ear
--------------	-----

S4905L

BG40#Blue Imp

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but but do no constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined the suitability of products are sold with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. AVERY DENNISON products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Any product shown to the satisfaction of AVERY DENNISON within the time provided to be so defective shall be replaced without charge of AVERY DENNISON may issue credit in such amount as it seems reasonable however, in no event shall AVERY DENNISON be responsable for claims beyond the replacement value of the defective product or in any way